
Molded Connectors With Loop

Molded Connectors with a Loop
Molded trailer connectors are manufactured with a loop of 18 gauge copper primary wire between a male and female end, except 8-contact which are manufactured with 3-12 gauge and 5-16 gauge copper wires. Four-contact, flat connectors are molded with an Easy Grip for fast and easy disconnects.





5-contact square connector



5-contact flat connector



6-contact square connector



8-contact square connector

Color Chart

		wire	
contacts	male end	colors	female end
1	─ 1 ●	1. blue	1 💿 🗀
2	1 0	1. brown 2. red	1 0 2
3	1 • 2 • 3 ° 0	1. green 2. yellow 3. brown	1 0 2 0 3 •
4 flat	1 • 2 • 2 • 3 4 • 0	1. green 2. yellow 3. brown 4. white	1 0 2 0 3 0 4 •
4 square	3 • • 1 4 • • 2	1. green 2. brown 3. yellow 4. white	1 0 0 3 2 0 4
5 square	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	1. green 2. blue 3. yellow 4. bown 5. white	1 0 0 3 2 0 0 4 5
5 flat	1 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	1. blue 2. green 3. yellow 4. brown 5. white	1 0 0 2 0 3 0 4 5 •
6	4 • • 1 2 5 6 • 0 3	1. yellow 2. brown 3. white 4. green 5. blue 6. black	1 0 0 4 2 0 0 5 3 0 0 6
8	5 0 1 2 7 0 3 3 8 0 4	1. green 2. blue 3. gray 4. yellow 5. brown 6. black 7. red 8. white	1 0 0 5 2 0 0 6 3 0 0 7 4 0 • 8